



INDUSTRIAL



RFD FUEL DISCHARGE 150 PSI HOSE

| NRP PART NUMBER | HOSE I.D. (NOMINAL) | | HOSE O.D. (NOMINAL) | | RATED W.P. | | WT. PER FT. |
|-----------------|---------------------|------|---------------------|------|------------|-----|-------------|
| | (IN.) | (MM) | (IN.) | (MM) | (PSI) | BAR | (LBS) |
| RFD-12 | 0.75 | 19 | 1.06 | 27 | 150 | 10 | 0.52 |
| RFD-16 | 1 | 25 | 1.37 | 35 | 150 | 10 | 0.65 |
| RFD-20 | 1.25 | 32 | 1.65 | 42 | 150 | 10 | 0.80 |
| RFD-24 | 1.50 | 38 | 1.88 | 48 | 150 | 10 | 0.94 |
| RFD-32 | 2 | 51 | 2.44 | 62 | 150 | 10 | 1.26 |
| RFD-40 | 2.50 | 63 | 2.95 | 75 | 150 | 10 | 1.90 |
| RFD-48 | 3 | 76 | 3.46 | 88 | 150 | 10 | 2.20 |
| RFD-56 | 3.50 | 89 | 4.09 | 104 | 150 | 10 | 2.60 |
| RFD-64 | 4 | 102 | 4.56 | 116 | 150 | 10 | 2.85 |
| RFD-80 | 5 | 127 | 5.59 | 142 | 150 | 10 | 4.20 |
| RFD-96 | 6 | 152 | 6.53 | 166 | 150 | 10 | 5.30 |

Tube: NBR

Reinforcement: Plies of Synthetic Cords with Anti-static Copper Wires

Cover: Synthetic Rubber Blended | Weather, Oil, Ozone, Abrasion Resistant

Temperature: -4° F to 185° F (-20° C to 85° C)

Application(s): Gas or petroleum oil delivery from tank truck | aromatic up to 50%

Offered Length(s): 100 & 200 foot

Safety Factor: 3 : 1

Branding: NRP JONES PETRO FD RFD (SIZE) FUEL DISCHARGE 150 PSI

ISO 9001:2015 CERTIFIED QUALITY SYSTEM
API Q1 9TH EDITION CERTIFIED QUALITY MANAGEMENT SYSTEM