

BUILT TOUGH FOR THE ROAD:

HIGH EFFICIENCY ROADWORK STARTS WITH HIGH QUALITY HOSES

HOT ASPHALT HOSE


Application: Applying hot asphalt at nozzle with pressures up to 300 PSI at 350° F constant and up to 400° F intermittent temperatures.

Tube: Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

Reinforcement: Two braids of high tensile steel wire.

Cover: Yellow, heat, oil, abrasion and weather resistant Neoprene (CR).

Temperature: -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1310-12	0.75	1.28	300	10	0.67
1310-16	1.00	1.53	300	12	0.89

HOT ASPHALT APPLICATOR HOSE


Application: Applying hot asphalt at nozzle with pressures up to 250 PSI at 350° F constant and up to 400° F intermittent temperatures.

Tube: Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

Reinforcement: Two braids of high tensile steel wire.

Cover: Black, heat, oil, abrasion and weather resistant Neoprene (CR).

Temperature: -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1856-16	1.00	1.53	250	12	0.89

CRACK SEALER HOSE


Application: Applying hot asphalt at nozzle with pressures up to 250 PSI at 350° F constant and up to 400° F intermittent temperatures.

Tube: Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

Reinforcement: Two braids of high tensile steel wire

Cover: Black, heat, oil, abrasion and weather resistant Neoprene (CR).

Temperature: -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1857-12	0.75	1.28	250	10	0.80
1857-16	1.00	1.53	250	12	1.03

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Office: 219-362-9908
Fax: 219-324-0815
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Office: 435-623-1740
Fax: 435-623-2638
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com

