



NRP Jones ISO-9001:2015 | Certified Quality System | API 7K FSL 1 temp range 2 Certified

ENGINEERED FOR DEMANDING OILFIELD PERFORMANCE

Precision-Build Hoses for Drilling, Fracturing & Transfer

Our oilfield hose lineup is designed to meet the rigorous demands of high-pressure, high-volume operations. From cementing to mud circulation, each hose delivers consistent performance, superior wear resistance, and reliable pressure ratings to keep your operations moving—safely and efficiently.

SCAN FOR MORE



Corporate Office & Manufacturing:

302 Philadelphia Street

Office: 219-362-9908

LaPorte, Indiana 46350

Fax: 219-324-0815

Customer Service Toll-Free Number

1-800-348-8868

Order Entry Toll-Free Fax Number

1-800-207-2221

Email

sales@nrpjones.com



OIL FIELD HOSES

NRP Jones Cementing Hose

Tube: Black NBR compounded for high abrasion and oil resistance.

Reinforcement: Multiple high tensile steel wire spiral layers with braided layer

Cover: Black oil and abrasion resistant NBR cover with white Mylar lay line.

Temperature: -4° F to + 212° F (max 248° F)

Recommended Use: A flexible connection between cementing pump manifold and cementing head for conveyance of cementing slurries at high pressure.

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
PS5646-32	2	2.80	10,000	15,000	32.30	4.74

NRP Jones Rough Neck High Pressure Transfer Hose

Tube: Black, NBR for oil and liquid mud resistant.

Reinforcement: Multiple high tensile steel wire spiral layers and braided layer

Cover: Black oil and abrasion resistant NBR cover with Green Mylar lay line.

Temperature: -4° F to+ 212° F (max 248° F)

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
PS5038-48	3	3.61	3,000	7,250	33.10	5.38
PS5038-64	4	5.22	3,000	7,500	54.75	13.65

NRP Jones Service Line Rotary Hose

Tube: Black, NBR for oil and liquid mud resistant.

Reinforcement: Multiple high tensile steel wire spiral layers

Cover: Black oil and abrasion resistant NBR cover with Silver Mylar lay line.

Temperature: -4° F to+ 212° F (max 248° F)

Recommended Services: Flexible connection between standpipe and swivel rotary drilling application. Also used as high pressure pumping between the standpipe and pump as a vibrator for oil drilling and exploration.

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
PS5600-40	2-1/2	3.21	5,000	7,500	32.30	4.74
PS5600-48	3	3.83	5,000	7,500	35.43	9.75





OIL FIELD HOSES

NRP Jones Mudd Dog Hose

Tube: Black, NBR for oil and liquid mud resistant.

Reinforcement: Multiple high tensile steel wire spiral layers and braided layer

Cover: Black, abrasion, ozone and hydrocarbon resistant synthetic NBR. Red Mylar lay line.

Temperature: -40° F to + 212° F (max 248° F)

Recommended Services: Flexible connection between standpipe and swivel rotary drilling application. Also used as high pressure pumping between the standpipe and pump as a vibrator for oil drilling and exploration.

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
MD5000-24	1 1/2	2.10	5,000	7,500	20.30	2.22
MD5000-32	2	2.65	5,000	7,500	27.60	3.32

1804 Rough Neck Hot Oiler Hose

Tube: Black, Nitrile Butadiene NBR

Reinforcement: Two piles of braided high-tensile strength steel wire

Cover: Black | Heat, oil, weather and abrasion resistant Neoprene (CR) cover with Green Mylar lay line.

Temperature: -40° F to+ 300° F

Application(s): Hot oil transfer at 275° F Continuous/300° F Intermittent

Offered Lengths: 50 feet

Safety Factor: 3:1

Packing: Coils

HOSE I.D. (IN.)	RATED W.P. (PSI)	TEST PRESSURE (PSI)	BEND RADIUS (MIN)	FITTING SIZE	WT. PER FT. (LBS)
1 1/2	2,250	3,375	20	1 1/2	1.9



MARKET PRODUCT & SIZE MATRIX

Department	Product
21	100R1
21	100R2
21	100R4
21 & 23	100R5
23	100R16
23	100R17
05	Armored Water Suction & Discharge
23	BOP
21	Concrete Pumping Hose
05	Dock Hose
06	Decoking
05	Dry Concrete
05	Exhaust (3")
05	Floater

Department	Size Range
05 - Hand Built Hose	Up to 24"
06 - Rotary Hose	Up to 4" (with 5" fittings)
21 - Solid Mandrel	3/4" to 4"
23- Flex Mandrel	3/16" to 1"

Additional Oil Field Products Available

Mudd Dog Hose

Rough Neck High Pressure Transfer Hose

Service Line Rotary Hose

Cementing Hose


1804 Rough Neck Hot Oiler Hose

TT/TTC Tank Truck Hose

UHMWPE/UHMWPEC Chemical Hose

PTFE

Department	Product
06	Grade C Rotary Hose
06	Grade D Rotary Hose
06	Grade E Rotary Hose
21	Gunnite
21	Hydro Carbon Drain Hose
05	Material Handling (Dry Bulk)
21	Natural Gas Hose (LPG)
21	Plaster & Grout
23	Power Jack
23	Pressure Wash
	Special Application
05	Water Discharge
05	Water Suction & Discharge



CONTACT US!



EXPERIENCE THE DIFFERENCE

Corporate Office & Manufacturing:

302 Philadelphia Street

Office: 219-362-9908

LaPorte, Indiana 46350

Fax: 219-324-0815

Customer Service Toll-Free Number 1-800-348-8868

Order Entry Toll-Free Fax Number 1-800-207-2221

Email

sales@nrpjones.com

Manufacturing Facility:

255 West 11th North

Office: 435-623-1740

Nephi, Utah 84648

Fax: 435-623-2638

Customer Service Toll-Free Number 1-800-453-1480

Order Entry Toll-Free Fax Number 1-800-207-2221

Email

sales3@nrpjones.com

