

WATER DISCHARGE HOSE

WD WATER DISCHARGE 150 PSI HOSE

Tube: Synthetic Rubber Blended

Reinforcement: Plies of Synthetic Cord

Cover: Synthetic Rubber Blended

Temperature: -4° F to 185° F (-20° C to 85° C)

Application(s): Water, natural liquid fertilizer, waste water — submerged pump and irrigation

Offered Length(s): 100 & 200 Foot

Safety Factor: 3:1

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (MM.)	HOSE O.D. (IN.)	HOSE O.D. (MM.)	RATED W.P. (PSI)	RATED W.P. (BAR)	WT. PER FT. (LBS)
WD-16	1	25	1.25	32	150	10	0.48
WD-20	1.25	32	1.53	39	150	10	0.62
WD-24	1.50	38	1.77	45	150	10	0.80
WD-32	2	51	2.28	58	150	10	0.94
WD-40	2.50	63	2.75	70	150	10	1.20
WD-48	3	76	3.26	83	150	10	1.50
WD-56	3.50	89	3.81	97	150	10	1.70
WD-64	4	102	4.29	109	150	10	2.20
WD-80	5	127	5.39	137	150	10	3.80
WD-96	6	152	6.37	162	150	10	4.50
WD-128	8	203	8.54	217	150	10	6.10

WSC AQUA CORRUGATED 150 PSI HOSE

Tube: Synthetic Rubber Blended

Reinforcement: Plies of Synthetic Cords with Helix Wire

Cover: Synthetic Rubber, Wrapped Type, Abrasion & Weather Resistant

Temperature : -4° F to 185° F (-20° C to 85° C)

Application(s): Handling of water, natural liquid fertilizer, inert fluid, sewage, waste water, mud where flexibility is required

Offered Length(s): 100 & 200 Foot

Safety Factor: 3:1

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (MM.)	HOSE O.D. (IN.)	HOSE O.D. (MM.)	RATED W.P. (PSI)	RATED W.P. (BAR)	WT. PER FT. (LBS)	BEND RADIUS (MIN) (IN)	VAC-UUM
WSC-12	0.75	19	1.14	29	150	10	0.69	5.11	0.9
WSC-16	1	25	1.37	35	150	10	0.80	6.29	0.9
WSC-20	1.25	32	1.65	42	150	10	0.96	8.26	0.9
WSC-24	1.50	38	1.88	48	150	10	0.75	9.84	0.9
WSC-32	2	51	2.44	62	150	10	1.01	11.81	0.9
WSC-40	2.50	63	2.95	75	150	10	1.96	15.74	0.9
WSC-48	3	76	3.46	88	150	10	1.61	18.90	0.9
WSC-56	3.50	89	4.01	102	150	10	2.90	17.71	0.9
WSC-64	4	102	4.56	116	150	10	2.22	23.62	0.9
WSC-80	5	127	5.55	141	150	10	5.20	39.37	0.9
WSC-96	6	152	6.53	166	150	10	4.50	47.24	0.9
WSC-128	8	203	8.77	223	150	10	11.20	59.05	0.9

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street

LaPorte, Indiana 46350

Customer Service Toll-Free Number 1-800-348-8868

Order Entry Toll-Free Fax Number 1-800-207-2221

Email sales@nrpjones.com

Office: 219-362-9908

Fax: 219-324-0815

Manufacturing Facility:

255 West 11th North

Nephi, Utah 84648

Customer Service Toll-Free Number 1-800-453-1480

Order Entry Toll-Free Fax Number 1-800-207-2221

Email sales3@nrpjones.com

Office: 435-623-1740

Fax: 435-623-2638

