

SUBMARINE HOSE

SUBMARINE HOSE

Tube: Nitrile (NBR) | Black | 1/8" | Petroleum service for aromatic content of 50%

Reinforcement: Multiple Plies of High Strength Textile Tire Cord and High Tensile Helix Wire.

Cover: Neoprene (CR) | Black | 1/4" | Standard Resistance to Abrasion, Oil, Tearing, Salt Water & Sunlight

Temperature: -40° F to +180° F

Lengths: Max – 50 feet

Application: Used in marine service for loading and unloading petroleum products

Fittings: Swaged on Nipples with 150# RF Weld Neck Flanges

Construction (layers): black tube, breaker, 4 plies steel fabric (wire tire-cord), helix wire over black, rubber cushion layer, 2 plies of regular tire-cord, cover layer

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	SAFETY FACTOR (RATIO)	VACUUM (IN-HG)	WT. PER FT. (LBS)
	3	4.31	225	18	4:1	Full	5.51
4300 Series	4	5.39	225	24	4:1	Full	7.65
4600 Series	6	7.52	225	36	4:1	Full	11.88
4700 Series	8	9.72	225	48	4:1	Full	13.98
	10	12.12	225	60	4:1	Full	15.23

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com

