

TANK TRUCK HOSE

TT PETRO 150 PSI TANK TRUCK HOSE

Tube: NBR Blend

Reinforcement: Plies of Synthetic Cords with Steel Helix and Anti-static Copper Wire

Cover: SBR Blended, Weather, Oil, Ozone, Abrasion Resistant

Temperature: -20° F to 185° F (-29° C to 85° C)

Application(s): Commercial gasolines, diesel oils & other petroleum products (51% aromatic)

Offered Length(s): 100 & 200 Foot

Safety Factor: 3:1

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (MM.)	HOSE O.D. (IN.)	HOSE O.D. (MM.)	RATED W.P. (PSI)	RATED W.P. (BAR)	WT. PER FT. (LBS)	BEND RADIUS (MIN)	VAC-UUM
TT-16	1	25	1.38	35	150	10	0.50	5.91	0.9
TT-24	1.5	38	1.89	48	150	10	1.10	10.03	0.9
TT-32	2	51	2.44	62	150	10	0.94	11.81	0.9
TT-48	3	76	3.54	90	150	10	2.70	18.11	0.9
TT-64	4	102	4.02	117	150	10	2.55	23.62	0.9
TT-96	6	152	6.61	168	150	10	4.97	33.46	0.9
TT-16100	1	25	1.38	35	150	10	0.50	5.91	0.9
TT-24100	1.5	38	1.89	48	150	10	1.10	10.03	0.9
TT-32100	2	51	2.44	62	150	10	0.94	11.81	0.9
TT-48100	3	76	3.54	90	150	10	2.70	18.11	0.9
TT-64100	4	102	4.02	117	150	10	2.55	23.62	0.9
TT-96100	6	152	6.61	168	150	10	4.97	33.46	0.9

THD PETRO 300 PSI TANK TRUCK HOSE

Tube: Oil & water resistant synthetic rubber

Reinforcement: Synthetic yarn fabric with steel wire helix

Cover: Synthetic rubber resistant to ozone, oil, weather and abrasion

Temperature : 20° F to 185° F (-29° C to 85° C)

Application(s): Commercial gasolines, diesel oils & other petroleum products including 51% aromatic content such as gasoline

Offered Length(s): 100 & 200 Foot

Safety Factor: 3:1

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (MM.)	HOSE O.D. (IN.)	HOSE O.D. (MM.)	RATED W.P. (PSI)	RATED W.P. (BAR)	WT. PER FT. (LBS)	BEND RADIUS (MIN)	VAC-UUM
THD-12	0.75	19	1.14	29	300	20	0.60	4.92	0.9
THD-16	1	25	1.37	35	300	20	0.86	5.90	0.9
THD-20	1.25	32	1.65	42	300	20	1.03	7.87	0.9
THD-24	1.50	38	1.92	49	300	20	1.20	10.003	0.9
THD-32	2	51	2.48	63	300	20	1.80	11.81	0.9
THD-40	2.50	63	3.03	77	300	20	2.40	13.97	0.9
THD-48	3	76	3.54	90	300	20	2.90	18.11	0.9
THD-56	3.50	89	4.09	104	300	20	3.60	20.86	0.9
THD-64	4	102	4.64	118	300	20	4.10	24.01	0.9
THD-80	5	127	5.62	143	300	20	6.80	27.55	0.9
THD-96	6	152	6.77	172	300	20	9.00	31.49	0.9

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street

LaPorte, Indiana 46350

Customer Service Toll-Free Number

Order Entry Toll-Free Fax Number

Email

Office: 219-362-9908

Fax: 219-324-0815

1-800-348-8868

1-800-207-2221

sales@nrpjones.com

Manufacturing Facility:

255 West 11th North

Nephi, Utah 84648

Customer Service Toll-Free Number

Order Entry Toll-Free Fax Number

Email

Office: 435-623-1740

Fax: 435-623-2638

1-800-453-1480

1-800-207-2221

sales3@nrpjones.com



TANK TRUCK HOSE



TSD PETRO 600 PSI TANK TRUCK HOSE

Tube: Oil & water resistant synthetic rubber

Reinforcement: Synthetic yarn fabric with steel wire helix

Cover: Synthetic rubber resistant to ozone, oil, weather and abrasion

Temperature: -20° F to 185° F (-29° C to 85° C)

Application(s): Commercial gasolines, diesel oils & other petroleum products including 51% aromatic content such as gasoline

Offered Length(s): 100 & 200 Foot

Safety Factor: 3:1

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (MM.)	HOSE O.D. (IN.)	HOSE O.D. (MM.)	RATED W.P. (PSI)	RATED W.P. (BAR)	WT. PER FT. (LBS)	BEND RADIUS (MIN)	VAC-UUM
TSD-32	2	51	2.99	76	600	40	3.41	11.81	0.9
TSD-48	3	76	4.01	102	600	40	5.20	18.11	0.9
TSD-64	4	102	5.03	128	600	40	6.80	24.01	0.9
TSD-96	6	152	7.00	178	600	40	11.00	31.49	0.9

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Office: 219-362-9908
Fax: 219-324-0815
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Office: 435-623-1740
Fax: 435-623-2638
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com

