

# BUILT TOUGH FOR THE ROAD:

## HIGH EFFICIENCY ROADWORK STARTS WITH HIGH QUALITY HOSES

### HOT ASPHALT HOSE

**Application:** Applying hot asphalt at nozzle with pressures up to 300 PSI at 350° F constant and up to 400° F intermittent temperatures.

**Reinforcement:** Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

**Tube:** Two braids of high tensile steel wire.

**Reinforcement:** Yellow, heat, oil, abrasion and weather resistant Neoprene (CR).

**Temperature:** -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1310-12	0.75	1.28	300	10	0.67
1310-16	1.00	1.53	300	12	0.89

### HOT ASPHALT APPLICATOR HOSE

**Application:** Applying hot asphalt at nozzle with pressures up to 250 PSI at 350° F constant and up to 400° F intermittent temperatures.

**Reinforcement:** Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

**Tube:** Two braids of high tensile steel wire.

**Reinforcement:** Black, heat, oil, abrasion and weather resistant Neoprene (CR).

**Temperature:** -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1856-16	1.00	1.53	250	12	0.89

### CRACK SEALER HOSE

**Application:** Applying hot asphalt at nozzle with pressures up to 250 PSI at 350° F constant and up to 400° F intermittent temperatures.

**Tube:** Black, blend of high temperature polymers especially compounded to resist swelling and embrittlement in hot asphalt service.

**Reinforcement:** Two braids of high tensile steel wire

**Cover:** Black, heat, oil, abrasion and weather resistant Neoprene (CR).

**Temperature:** -40 to 350° F.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
1857-12	0.75	1.28	250	10	0.80
1857-16	1.00	1.53	250	12	1.03

## MADE IN THE USA

#### Corporate Office & Manufacturing:

302 Philadelphia Street  
 LaPorte, Indiana 46350  
 Office: 219-362-9908  
 Fax: 219-324-0815  
 Customer Service Toll-Free Number 1-800-348-8868  
 Order Entry Toll-Free Fax Number 1-800-207-2221  
 Email sales@nrpjones.com

#### Manufacturing Facility:

255 West 11th North  
 Nephi, Utah 84648  
 Office: 435-623-1740  
 Fax: 435-623-2638  
 Customer Service Toll-Free Number 1-800-453-1480  
 Order Entry Toll-Free Fax Number 1-800-207-2221  
 Email sales3@nrpjones.com

