



UHMW PEC HOSE

NRP JONES UHMW PEC HOSE


Application: Hardwall hose designed with ultra-high molecular weight polyethylene lining, excellent in suction and delivery a wide range of chemicals, petroleum products and oils.

Reinforcement: High strength synthetic cord and helix wire.

Temperature: -30°C (-22°F) to +93°C (+199°F)

Tube: White, smooth, food quality UHMWPE lining.

Cover: Green, corrugated (wrapped finish), EPDM rubber.



PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BURST RADIUS (PSI)	MAX LENGTH (FT.)
UHMWPEC-16100	1	1.46	250	720	100
UHMWPEC-24100	1.5	2.05	250	720	100
UHMWPEC-32100	2	2.60	250	720	100
UHMWPEC-48100	3	3.60	250	720	100
UHMWPEC-64100	4	4.80	250	720	100

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com



nrpjones.com