

FIRE FLEX BOP HOSE

FIRE FLEX BLOW OUT PREVENTER HOSE, 3000 AND 5000

Application: Flexible piping used to control BOP's (Blowout Preventers) and associated valves that control well pressure during drilling operations

Tube: Black, oil resistant Nitrile (NBR).

Reinforcement: Multiple plies of high tensile steel wire

Cover: Red, specially compounded, fiber glass impregnated, flame resistant rubber

Temperature: -40° F to 212° F

Fittings: Skive type; see crimp applicatiosn for part number

Meets Lloyd's API 16D/LR 1000/499 Requirement

Meets ABS and EUB Requirements



PRODUCT VARIATIONS

3000 BOP HOSE

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
A822-06	3/8	0.90	3,000	6	0.51
A822-08	1/2	1.04	3,000	9	0.62
A822-12	3/4	1.32	3,000	12	0.88
A822-16	1	1.61	3,000	15	1.30
1822-20	1-1/4	2.10	3,000	18	2.30
1822-24	1-1/2	2.41	3,000	22	2.95
1822-32	2	2.90	3,000	27	3.69

5000 BOP HOSE

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	RATED W.P. (PSI)	MIN. BEND RADIUS (IN.)	WT. PER FT. (LBS)
A825-06	3/8	0.90	5,000	6	0.51
A825-08	1/2	1.04	5,000	9	0.64
1825-12	3/4	1.54	5,000	12	1.50
1825-16	1	1.79	5,000	15	1.97
1825-20	1-1/4	2.21	5,000	18	3.06
1825-24	1-1/2	2.54	5,000	22	3.98
1825-32	2	3.05	5,000	27	5.83

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Office: 219-362-9908
Fax: 219-324-0815
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Office: 435-623-1740
Fax: 435-623-2638
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com

