

TRIOFLEX HOSE

5013/5014

TRIOFLEX HOSE SLIM HOLE ROTARY HOSE

Tube: Black, oil and abrasion resistant Neoprene (CR). Suitable for oil and water based muds.

Reinforcement: Three or four braids of high tensile, heavy gauge steel wire. A textile over braid provides improved cover adhesion.

Cover: Black, oil, abrasion and weather resistant Neoprene (CR).

Temperature: -40° F to 200° F

Fittings: Hose is supplied with swaged-on couplings. Hose may also be supplied without couplings.

Lengths: 50 ft. standard

Premium Features: Abrasion, oil and weather resistant. Extremely flexible and durable. Easy identification branding.

PART NUMBER	HOSE I.D. (IN.)	HOSE O.D. (IN.)	WIRE BRAIDS	WORKING PRESSURE (PSI)	DESIGN BURST PRESSURE	MIN. BEND RADIUS	CPLG. WT. (2)	NPT THREAD (IN.)	WT. PER FOOT (LBS.)
5013-32	2	3.06	3	2,500	7,000	18	35	2	3.9
5014-40	2.5	3.65	4	2,500	6,000	24	44	2.5	5.3
5014-48	3	4.13	4	2,500	5,000	30	51	3	5.8

Application: NRP Trioflex Hose was specially designed for applications on portable drilling rigs, work-over rigs, slim hole and seismograph rigs. It is and extremely flexible and durable hose.

MADE IN THE USA

Corporate Office & Manufacturing:

302 Philadelphia Street
LaPorte, Indiana 46350
Office: 219-362-9908
Fax: 219-324-0815
Customer Service Toll-Free Number 1-800-348-8868
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales@nrpjones.com

Manufacturing Facility:

255 West 11th North
Nephi, Utah 84648
Office: 435-623-1740
Fax: 435-623-2638
Customer Service Toll-Free Number 1-800-453-1480
Order Entry Toll-Free Fax Number 1-800-207-2221
Email sales3@nrpjones.com

